

Manages the flow of people entering an establishment in an agile and innovative way



Our solution is composed of an IP camera and a customizable information screen with access allowed or denied software, manages the total capacity control for any company type or size.

Thanks to Artificial Intelligence and its powerful algorithm, it reliably counts the passage of people and the distance in real time, fulfilling the established protocols.

The software controls the data and shows them on the screen in real time through a customized interface that includes the logo:



Green light: Access allowed. Less than the maximum capacity allowed



Red light: Access denied. Equal or full capacity

- Simple configuration. Maximum capacity allowed
- CCAforo Hub*
- 10.1" or 15.6" screen
- Up to 2m door width

- Automatic alert when maximum capacity has been exceeded
- Installation: Self-supporting bracket
- Accuracy up to 94%**
- * Only included with 15,6 " screen ** Provided that the camera is correctly installed and with sufficient

Real-time • Automatic Control • Reliable • Easy to install











TECHNICAL SPECIFICATIONS

Camera	Format IP mini domo
Resolution	1280x720
Code	H.264
Supported formats	RTSP/HTTP/TCP/UDP/FTP/DHCP
Screen size	10.1" / 15,6"
Maximum camera width	2 meters to 2,7 meters (height*)
Processor	Intel Atom® Z3735F
Kit content	1 x IP Camera
	1 x Power charger
	1 x Screen 10.1" / 15,6"
	1 x CCAforo Hub**
	1 x Switch Ethernet (4 ports)
	1 x Self-supporting bracket
	3 x UTP 1.8m cable
	1 x Manual
Optional accessories	Non-contact hydroalcoholic gel dispensing
Guaranteee	2 years
Certification	CE, RoHS

^{*}Recommended installation height. For other widths is recommended an additional camera



^{**} Only included with 15,6 " screen