

<b>Model Name</b>	<b>ITC-300</b>
<b>Product Name</b>	<b>Digital Intercom System</b>
<b>Power</b>	12V
<b>Tally</b>	2 x 15 Pin D-Sub Female Sockets for Tally A and Tally B
<b>MIC / Headset</b>	1 x 3.5mm Stereo Jack Socket ( For Headphone / Microphone combination) Headset Impedance 8~600 ohms 100mW(min)
<b>Headphone</b>	1 x 1/4" (6.3mm) Stereo Headphone Socket Headset Impedance 8~600 ohms 100mW(min)
<b>Light Socket (DC 12 V)</b>	Light Power Consumption: +5 V / 500 mA
<b>Microphone</b>	3 Pin XLR / 1/4" (6.3mm) Socket x 1 Switchable Condenser / Dynamic Input Microphone Level -67dB PIN1:N/A,PIN2:MIC,PIN3:GND
<b>Frequency Response</b>	300 Hz-7 KHz, < +/-3dB
<b>THD</b>	< 0.1% @1KHz
<b>S/N</b>	>70dB
<b>Built-in Speaker</b>	3W Speaker is mute when headphones or mic / headset are connected to the ITC-300
<b>Operating Range</b>	Up to 100m between Base Station and Slave
<b>Operating Temp. Range</b>	5~45 °C