

D-Cerno D

D-Cerno Delegate Discussion Unit



Description

D-Cerno introduces a new era: an innovator within its market segment. It combines sleek design with digital signal processing and plug-and-play functionality.

Stylish, discreet, and unobtrusive with a low profile: the D-Cerno is at home in any meeting room context.

The system is completely based on digital signal processing. The result is crystal-clear sound and excellent intelligibility. Two cornerstones of any successful meeting.

In a global, interconnected world where communication is crucial, immunity to typical mobile phone interference is simply a must. D-Cerno's shielded microphone eliminates these disturbances, so delegates can focus on the essence of the meeting.

The system is designed to work out-of-the-box, with hardly any technical expertise required. Wiring is easy: simply connect shielded Cat 5 cables from unit to unit. While connecting, there is no need to worry about the IN and OUT port since the unit detects the direction of the signal flow automatically. It makes cabling errors virtually impossible.

D-Cerno uses the most recent touch sensor button technology which results in several benefits.

The unit is hygienic and easy to clean since there are no gaps around the buttons where dirt and bacteria can accumulate.

And because there are no moving parts, there is no wear of the buttons. As a result, D-Cerno guarantees consistent performance over the entire lifespan of the product.

The system has the added benefit of easy extensibility: increasing or decreasing the number of units is a breeze. It makes D-Cerno ideal for rental use.

The D-Cerno D has a 30 cm microphone, the D-Cerno DL (71.98.303) has a 50 cm microphone.

Benefits

- » Contemporary design fits in everywhere
- » Easily cleaned
- » Superior lifespan
- » Plug-and-play approach

Features

- » Digital signal processing
- » Stylish, unobtrusive, low profile design
- » Hygienic touch sensor technology
- » Shielded microphone, immune to mobile phone interference
- » High-quality integrated loudspeaker
- » Headphone output
- » Headphone volume adjustment
- » Microphone On/Off button
- » Loop-through, daisy-chain cabling
- » Patented fail-safe redundancy feature
- » Concealed conference bus connections
- » Microphone LED ring
- » Bi-color bar indicator

Connectivity

- » 2 digital bus connections (IN/OUT - interchangeable)
- » Headphone connection

TEL152 Headphones

71.04.0154

- » A 2 m patch cable is included with the unit

Certification

Region	Certification
Europe	CE

Specifications

Mechanical	
Material	PC/ABS
Color	Black
Size (mm)	210 (w) × 135 (h) × 50 (d)
Size packed (mm)	400 (w) × 150 (h) × 130 (d)
Weight	620g
Weight packed	1000g
Microphone length (mm)	300
Electrical	
Power Supply	48 DC, over Cat5 cable
Power consumption	2 W
Audio quality	16 bit digital
Frequency response	25 Hz-15,000 Hz (± 3 dB)
Headphone	
Impedance	16-150 Ω
Output level	Max 70 mW 32 Ω
Environment	
Operating temperature	5 to 50 °C