

Part No. 41729

MINI DISPLAYPORT TO HDMI ACTIVE CONVERTER

CONVERT A DISPLAYPORT SIGNAL TO HDMI



DESCRIPTION RELATED PRODUCTS

- Connect a Mini DisplayPort computer to an HDMI 4k display
- Supports resolutions up to 3840x2160@30Hz
- Audio pass-through if supported by the video source
- Active chipset for enhanced compatibilty with various graphic cards
- · 2 vear warranty

The Lindy Mini DisplayPort to HDMI Converter is ideal for connecting a Mini DisplayPort equipped source device to be connected to a HDMI display or TV. It supports 4k UHD resolutions up to 3840x2160@30Hz and allows Audio pass-through if supported by the video source. The converter can also be used to add another display to extend the available desktop workspace and increase productivity.

Active conversion guarantees compatibility with various graphics cards including AMD Eyefinity, NVIDIA surround and Intel Collage, great for an immersive gaming setup or a productive multi-screen working experience. The converter is also ideally suited for travelling due to its compact, lightweight form factor and convenient Plug & Play installation.

0

LINDY

Mini DisplayPort Male

MINI DISPLAYPORT TO HDMI ACTIVE CONVERTER

SPECIFICATIONS

AV Interface Mini DisplayPort to HDMI

Interface Standard DisplayPort 1.1a / HDMI 1.4b

Supported Bandwidth 5.4Gbps

Maximum Input Resolution 3840x2160@30Hz Output HDMI Type A Female

Maximum Output Resolution 3840x2160@30Hz MISCELLANEOUS

Packaging Type Polybag

Chipset PS171 QFN-56 Packaging Dimension 160x160x20mm (6.3x6.3x0.79in)

Gross Weight 0.030kg (0.07lb)

Warranty (Years) 0

HDCP Support HDCP 1.4 Certificated CE, FCC, RoHS & REACH Supported Audio Pass-through

Separate Audio Ports Special Features -

PHYSICAL PROPERTIES

PURCHASING INFORMATION

No. 41729

Dimensions (approx.) WxDxH 22x41.7x9.5mm EAN 4002888417297

22x41.7x9.5mm EAN 40028884 (0.87x1.64x0.37in) 20x26x9.5mm

CONNECTORS

Input

PACKAGING CONTENTS

(0.79x1.02x0.37in)

Mini DisplayPort to HDMI Active Converter

Cable Length 150mm (5.91in)

Housing Material ABS

Jacket Material PVC

Jacket Diameter 4.5mm (0.18in)

Minimum Bend Radius 45mm (1.77in)

Net Weight 0.026kg (0.06lb)

Operating Temperature $0^{\circ}\text{C} - 80^{\circ}\text{C} (32^{\circ}\text{F} - 176^{\circ}\text{F})$ Storage Temperature $-10^{\circ}\text{C} - 80^{\circ}\text{C} (14^{\circ}\text{F} - 176^{\circ}\text{F})$ Humidity $10 - 85^{\circ}\text{RH} \text{ (non-condensing)}$

Colour White