Product Datasheet



AVer MT300NNDI® Matrix Tracking Box



			Orange: power on
Power requirement	AC 100 - 240V to DC 12V/1.5A	LED indicator: STATUS	Green: operating
			Green (flashing): firmware upgrading
Power consumption	18W	LED indicator: USB	Green: connected and standby
			Green (flashing): UVC/UAC streaming
Dimensions (W x D x H)	15.0 x 21.0 x 4.1 cm	LED indicator: LAN	Green: connected
Net weight	0.9 (± 0.1) kg	Resolution	Inputs: up to 1080p 60 fps
			Outputs: up to 4K 60 fps
Storage conditions	Temperature: -20°C to +60°C	Operating conditions	Temperature: 0°C to +50°C
	Humidity: 20% to 95%		Humidity: 20% to 80%
Inputs	HDMI x 3	Outputs	
	USB 2.0 Type-A x 3		HDML v. 2
	RS-422 x 1		HDMI x 2
	RJ-45 x 1		USB 3.0 Type-B x 2
	PoE+ x 1		
Communication protocol	RS-422	PoE+	Yes, 42.5V to 57V/0.6A
NDI® HX2	Yes	Security	Kensington lock
Buttons	Power, Reset	Certification	CE, FCC, BSMI, NCC, IC, VCCI, UKCA,
			EAC
Wall mount	Yes	Warranty	3 years
	·		

Package Contents:

MT300N unit, Power Adapter, Power Cable, Cable Fixing Plate (x2), Cable Tie (x13), 3.0 x 5 mm Flat Head Screw (x5), 3.0 x 5 mm Truss Head Screw (x4), M3 x 10 mm Screw (x4), Rack Mount Bracket (x2), USB 3.0 Cable (x2), RS-422 Cable, Quick Start Guide, Warranty Card*

Optional Accessories:

Server Rack Mount, 3.0 x 5 mm Flat Head Screw (x3), 3.0 x 5 mm Truss Head Screw (x2)

Notes:

- * For Japan only.
- Specifications may vary depending on countries and are subject to change without notice.

