

# ZU607T

High brightness professional laser projector



- **Bright WUXGA laser projector - 6,500 lumens**
- **30,000 hours maintenance-free laser light source**
- **Control with HDBaseT 3.0, RS232 & OMSL**
- **4K, HDR & HLG Compatibility**

Introducing the ZU607T.

At 6,500 lumens, with 4K and HDR compatibility, the ZU607T features a dust resistant IP6X certified optical engine for 24/7 operational capabilities and low maintenance. The ZU607T projector features an extremely long-life laser technology, manual horizontal & vertical lens shift and built-in 15W speakers.

Suitable for a wide variety of applications, this projector is perfect for anywhere that requires a clean bright image including large venues, classrooms/lecture theatre's, museums, houses of worship, digital signage, simulation and immersive installations.

The added control flexibility of HDBaseT 3.0 and LAN make this projector an affordable set and forget solution

## Specifications

EAN: 5055387668515, Colour: White

The following specifications are preliminary and subject to change without notice

### Display/image

Display technology	DLP
Resolution	WUXGA (1920x1200)
Brightness	6,500 lumens
ANSI brightness	5,200
Contrast ratio	300,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3,16:9,16:10
Keystone correction - horizontal	+/-30°
Keystone correction - vertical	+/-30°
Has vertical auto keystone correction	Yes
Displayable colours (millions)	1073.4
Horizontal scan rate	5k~140kHzKHz
Vertical scan rate	24~120HzHz
Uniformity	85%
Screen size	0.8m ~ 7.67m (31.5" ~ 301.8") diagonal

### Lamp info

Light source type	Laser
LASER life	30,000 hours

### Optical

Throw ratio	1.2:1 ~ 1.92:1
Projection distance	1.3m - 7.8m / 51.18" - 307.09"
Zoom	1.6
Zoom type	Manual
Focal length	17.63 ~ 27.9
Lens shift	Vertical -100 ~ 120%, Horizontal: +/-10%
Native offset	120%
Lens shift	Yes - <a href="#">{{downloads_link}}</a>

### Connectivity

Connections	<b>Inputs</b> 2 x HDMI 2.0, 2 x VGA, 1 x Composite video, 2 x Audio 3.5mm, 1 x USB-A power 1.5A <b>Outputs</b> 1 x HDMI 2.0, 1 x Audio 3.5mm, 1 x 3D sync, 1 x 12V trigger <b>Control</b> 1 x HDBaseT 4K, 1 x RJ45, 1 x RS232
-------------	---

### LAN - wireless networking

No

### General

Noise level (min)	33dB
Noise level (max)	36dB
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
IP rating	IP6X
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
24/7 operation	Yes
360° operation	Yes
Remote control	Backlit ProAV remote
Heat dissipation	883BTU/hour
Speaker count	2
Watts per speaker	15W
In the box	AC power cord Remote control 2x AAA batteries Basic user manual

### Networking

LAN - control	Yes
LAN - wireless networking	No
LAN	Yes

### Power

Power supply	Universal AC 100--240V± 10%~ 50 / 60 Hz with PFC input
Power consumption (standby)	<0.5W
Power consumption (min)	300W
Power consumption (max)	366W

### Weight and dimensions

Dimensions (W x D x H)	374 x 302 x 117 mm / 14.72" x 11.89" x 4.61"
Gross weight	8.6 kg / 18.96 lbs
Net weight	6.3 kg / 13.89 lbs

