



PT-REZ12 Series

1-Chip DLP™ Projectors

AVAILABLE FROM CY2023 Q3

Note: Release date varies depending on country or region.

Evolved 1-Chip DLP™ Projectors with Powerful Contrast Transform Your Experience with a Smooth, Frictionless Workflow



Black Models



White Models



[Preliminary Specification] PT-REZ12 Series			
	PT-REZ12	PT-REZ10	PT-REZ80
Light Output	12,000 lm ³	10,000 lm ³	8,000 lm ³
Resolution	WUXGA (1920 x 1200)		

Note: Specifications are tentative. Ships with ET-C15G00 lens included.

• High-Contrast Visuals Deepen Engagement

The refined REZ12 Series 1-Chip DLP™ laser projector features Evolved Dynamic Contrast with new scene-recognition circuitry for powerful contrast performance. In addition, improved black-level adjustment ensures seamless projection, while Rich Color Enhancer expands red color expression for more vibrant colors.

• Flexibility and Expandability for Timesaving Workflow

Simplify complex workflows with expanded interfaces, functions, and options. Adapt projection to different applications and environments with new lenses featuring powered peripheral focus⁴, wider lens-shift, and enhanced native contrast. Expand and scale connectivity with proprietary or third-party⁵ Intel® SDM-specified function boards, import your own test patterns⁶, prep for setup without AC power via NFC function⁷, and save time with preactivated upgrade kits for Geo Pro⁸.

• All-New Compact Body Supports Maintenance-free Projection

REZ12 Series equips an hermetically sealed optical block and all-liquid cooling sourced from our 3-Chip DLP™ platform, enabling 20,000 hours⁹ of maintenance-free operation. Backup Input¹⁰ prevents screen-blanking by instantly switching to a secondary signal if the primary is disrupted, and high brightness is maintained if a diode fails thanks to Multi-Laser Drive Engine failovers.

1 Input signals are converted to the projector's display resolution upon playback. YPbPr 4:2:0 format only for 4K/60p signals input via DIGITAL LINK. 2 Only when optional TY-SB01DL DIGITAL LINK Terminal Board is loaded. 3 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped. 4 Function supported on selected lenses only. 5 Third-party Intel® SDM-specified function boards sold separately. Panasonic cannot guarantee operation of third-party devices. 6 Supports PNG (1/8/16/24/32/48/64-bit, non-transparent, alpha blending disabled) and BMP (1/8/24-bit) formats with maximum resolution of 1920 x 1200 dots. 7 Projectors sold in some countries or regions require an ET-NUK10 Upgrade Kit available from PASS to activate NFC function. See NFC Regional Compatibility List for details. 8 Visit PASS to register your projector and download free Geometry Manager Pro software. 9 Around this time, light output will have decreased by approximately 50%. IEC62087: 2008 Broadcast Contents, NORMAL Mode, Dynamic Contrast [3], temperature 35 °C (95 °F), elevation 700 m (2,297 ft) with 0.15 mg/m³ of airborne particulate matter. Panasonic recommends checkup at point of purchase after about 20,000 hours. Light-source lifetime may be reduced depending on environmental conditions. Replacement of parts other than the light source may be required in a shorter period. Estimated maintenance time varies depending on environment. 10 Primary and backup terminal assignment is fixed. Input signals to primary and backup inputs must be identical.

Specifications (Tentative)

Model	PT-REZ12	PT-REZ10	PT-REZ80		
Projector type	1-Chip DLP™ projectors				
DLP™ chip	Panel size	0.8 in diagonal (16:10 aspect ratio)			
	Display method	DLP™ chip x 1, DLP™ projection system			
	Number of pixels	2,304,000 (1920 x 1200 pixels)			
Light source	Laser diode				
Light output ^{1,2}	12,000 lm	10,000 lm	8,000 lm		
Time until light output declines to 50 % ³	20,000 hours (NORMAL/QUIET), 24,000 hours (ECO)				
Resolution	WUXGA (1920 x 1200 pixels)				
Contrast ratio ¹	20,000:1 (Full On/Full Off, Dynamic Contrast [3]) (TBD)				
Screen size (diagonal)	70–700 inches (with supplied lens)				
Center-to-corner zone ratio ¹	90 %				
Lens	Powered zoom (throw ratio 1.36–2.19:1 for supplied lens), powered focus (optional lenses also available)				
Lens shift (From the origin point of the lens mounter)	Vertical	±60 % (with supplied lens)			
	Horizontal	±29 % (with supplied lens)			
Keystone correction range	Vertical: ±40 °, Horizontal: ±40 ° (with supplied lens)				
Installation	Ceiling/floor, front/rear, free 360-degree installation				
Terminals	HDMI™ 1/2 IN	HDMI™ x 2 (Deep Color, compatible with HDCP 2.3, 4K/60p signal input ⁴)			
	DisplayPort™	DisplayPort™ x 1 (Deep Color, compatible with HDCP 2.3, 4K/60p signal input ⁴)			
	MULTI SYNC IN	BNC x 1			
	MULTI SYNC OUT	BNC x 1			
	SERIAL IN	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)			
	SERIAL OUT	D-sub 9-pin (male) x 1 for link control (RS-232C compliant)			
	REMOTE 1 IN	M3 stereo mini-jack x 1 for wired remote control			
	REMOTE 1 OUT	M3 stereo mini-jack x 1 for link control (for wired remote control)			
	REMOTE 2 IN	D-sub 9-pin (female) x 1 for external control (parallel)			
	LAN	RJ-45 x 1 for network connection, PjLink™ (Class 2) compatible, 10Base-T/100Base-TX, Art-Net compatible			
	USB	USB connector (Type A) x 1 for optional AJ-WM50 Series Wireless Module/USB memory			
	DC OUT	USB Type A x 1 (for power supply, DC 5 V, 2 A)			
	Expansion slot	Open slot for for function boards, Intel® SDM compatible			
	Protocol versions	IPv4, IPv6 ⁵			
Power supply	AC 100–240 V, 50/60 Hz				
Power consumption ⁶	Maximum power consumption	1,050 W (10.7–4.5 A) (1,070 VA) (TBD)	980 W (10–4.2 A) (1,000 VA) (TBD)	760 W (7.7–3.2 A) (770 VA) (TBD)	
	On-mode power consumption (Operating mode)	NORMAL	900 W (TBD)	830 W (TBD)	600 W (TBD)
		ECO	700 W (TBD)	640 W (TBD)	475 W (TBD)
		QUIET	890 W (TBD)	630 W (TBD)	470 W (TBD)
Cabinet materials	Molded plastic				
Operation noise ¹	39 dB (NORMAL/ECO), 35 dB (QUIET)	37 dB (NORMAL/ECO), 33 dB (QUIET)	35 dB (NORMAL/ECO), 32 dB (QUIET)		
Dimensions (W x H x D)	498 x 212 x 538 mm (19 5/8" x 8 11/32" x 21 3/16") (with feet at shortest position, not including protruding parts)				
Weight ⁷	28.8 kg (63.49 lbs) with supplied lens (TBD)				
Operating environment	Operating temperature: 0–45 °C (32–113 °F) ⁸ , operating humidity: 10–80 % (no condensation)				
Applicable software	Logo Transfer Software, Multi Monitoring & Control Software, Projector Network Setup Software, Early Warning Software, Geometry Manager Pro, Smart Projector Control for iOS/Android				
Control function via LAN	Crestron Connected™ V2, Crestron XiO Cloud™, Art-Net DMX, AMX® DD, and PjLink™ (Class 2)				

1 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped. 2 When [PICTURE MODE] is set to [DYNAMIC] and [OPERATING MODE] is set to [NORMAL]. 3 Around this time, light output will have decreased by approximately 50 %. IEC62087: 2008 Broadcast Contents, NORMAL Mode, Dynamic Contrast [3], temperature 35 °C (95 °F), elevation 700 m (2,297 ft) with 0.15 mg/m³ of airborne particulate matter. Estimated time until light output declines to 50 % varies depending on environment. 4 4K signals are converted to WUXGA (1920 x 1200 pixels). 5 Optional AJ-WM50 Series Wireless Module is not compatible with IPv6. 6 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. On-mode power consumption measured at 25 °C (77 °F) operating temperature at an altitude of 700 m (2,297 ft). 7 Average value. May differ depending on the actual unit. 8 When optional AJ-WM50 Series wireless module is attached, operating temperature range becomes 0–40 °C (32–104 °F). The operating environment temperature should be between 0 °C (32 °F) and 40 °C (104 °F) if the projector is used at an altitude between 1,400 m (4,593 ft) and 4,200 m (13,780 ft).

Optional Accessories

- Zoom Lens**
 ET-C1U100 (0.308–0.330:1)¹ / ET-C1W300 (0.550–0.690)² / ET-C1W400 (0.680–0.950:1)³ / ET-C1W500 (0.940–1.39:1)³ / ET-C1S600 (1.36–2.10:1)² / ET-C1T700 (2.07–3.38:1)³
 Note: Lenses are equipped with Auto Lens Identification Function. ET-C1S600 is equivalent of supplied lens.
¹ Estimated for release in CY2023 Q4. ² Estimated for release in CY2023 Q2. ³ Estimated for release in CY2023 Q3.
- Ceiling Mount Bracket**
 ET-PKD120H (for high ceilings)
 ET-PKD120S (for low ceilings)
 ET-PKD130H (with 6-axis adjustment mechanism)
 Note: ET-PKD120H/PKD120S/PKD130H used in combination with ET-PKD130B (sold separately).
- Function Boards**
 12G-SDI Terminal Board
 TY-SB01QS
 Wireless Presentation System Receiver Board
 TY-SB01WP
 DIGITAL LINK Terminal Board
 TY-SB01DL
- Attachment for Ceiling Mount Bracket**
 ET-PKD130B
- Wireless Module**
 AJ-WM50 Series
 Note: Availability may vary by country or region. The suffix at the end of the model number is omitted. Operating temperature: 0–40 °C (32–104 °F).
- DIGITAL LINK Switcher / Digital Interface Box**
 ET-YFB200G / ET-YFB100G
 Note: ET-YFB200G/YFB100G is not compatible with 4K signals.
- Wireless Presentation System PresIT**
 TY-WPS1 (Basic set)
 Note: Availability may vary by country or region.
- NFC Upgrade Kit**
 ET-NUK10
 Note: Availability may vary by country or region.
- Early Warning Software**
 ET-SWA100 Series
 Note: Part number suffix may differ depending on the license type.

Panasonic CONNECT

Weights and dimensions shown are approximate. Specifications and appearance are subject to change without notice. Availability of products and accessories may vary by country or region. Products may be subject to export control regulations. DLP, DLP logo, and DLP Medallion logo are trademarks or registered trademarks of Texas Instruments. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade Dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. Intel and the Intel logo are trademarks of Intel Corporation or its subsidiaries. Trademark PjLink is a trademark applied for trademark rights in Japan, the United States of America and other countries and areas. Android is a trademark or registered trademark of Google LLC. IOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license. Windows® is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries. SOLID SHINE and PresIT are trademarks of Panasonic Holdings Corporation. All other trademarks are the property of the respective trademark owners. © Panasonic Connect Co., Ltd. 2023.



For more information about Panasonic projectors, please visit:
 Projector Global Website – <https://panasonic.net/cns/projector/>
 Facebook – www.facebook.com/panasonicprojectoranddisplay
 YouTube – www.youtube.com/user/PanasonicProjector

Note: Following the shift of the Panasonic Group to a holding company system, the Connected Solutions Company of the Panasonic Corporation has changed to Panasonic Connect Co., Ltd. as of April 1, 2022.

All information included here is valid as of January 2023.

PT-REZ12PRE1 Printed in Japan.